

TECHNICAL DATA SHEET

TechNiGlove
♦ INTERNATIONAL ♦

RVCR3500

PHYSICAL PROPERTIES

Style	Ambidextrous
Length	12" (300mm)
Thickness	4 mil (0.005")
Grip Surface	Microtextured Fingertips
Cuff	Beaded
Colors	White
Tensile Strength	>14 MPa
Elongation	Min 600%



**Soft Modulus, Accelerator Free
Powder Free Nitrile Gloves**

TECHNICAL PROPERTIES

Particle Levels Class M2.5 (10)	<400 total particles/cm ² > 0.5-20um IEST-RP-CC005.4
Surface Resistivity In Use	<1x09 ⁹ ohm/square per ANSI/ESD SP15.1
Flouride	< 0.005 ug/cm ²
Chloride	< 0.1 ug/cm ²
Nitrite	< 0.005 ug/cm ²
Nitrate	< 0.1 ug/cm ²
Bromide	< 0.02 ug/cm ²
Phosphate	< 0.005 ug/cm ²
Sulphate	< 0.02 ug/cm ²
Total NVR (DI Water)	< 1.00 ug/cm ²
Cert of Conformance	Available on request

ORDERING INFORMATION

12" Class 10 Nitrile Gloves		Case Wt.
RVCR3500	X-SMALL	14 lbs.
RVCR3501	SMALL	17 lbs.
RVCR3502	MEDIUM	18 lbs.
RVCR3503	LARGE	18 lbs.
RVCR3504	X-LARGE	21 lbs.
RVCR3505	XX-LARGE	23 lbs.

Packaged 100 gloves per pack, 10 packs per case.
Case Size: 10.5"x13"x12"

TechNiGlove
♦ INTERNATIONAL ♦

3750 Pierce Steet, Riverside, CA 92503 USA
Toll Free (877) 648-7453 Phone (951) 582-0890 Fax (951) 582-0990
www.TechNiGlove.com